



Size Rope Dia.	Fiber Core (IPS)		IWRC (EIPS)	
	Approx. Weight per Foot in Pounds	Breaking Strength in Pounds	Approx. Weight per Foot in Pounds	Breaking Strength in Pounds
1/4"	.105	4,940	.116	6,120
5/16"	.164	7,660	.18	9,480
3/8"	.236	10,980	.26	13,600
7/16"	.32	14,880	.35	18,360
1/2"	.42	19,260	.46	24,000
9/16"	.53	24,300	.59	30,200
5/8"	.66	30,000	.72	37,000
3/4"	.95	42,800	1.04	53,000
7/8"	1.29	48,000	1.42	71,600
1"	1.68	75,200	1.85	93,000
1.1/8"	2.13	94,600	2.34	117,000
1.1/4"	2.63	116,200	2.89	143,800
1.3/8"	3.18	139,800	3.50	172,800
1.1/2"	3.78	165,600	4.16	206,000
1.5/8"	4.44	192,600	4.88	238,000
1.3/4"	5.15	224,000	5.67	276,000
2"	6.72	288,000	7.39	314,000
2.1/4"	8.51	360,000	9.36	444,000
2.1/2"	10.50	440,000	11.6	544,000
2.3/4"	12.70	526,000	14.0	650,000
3"	15.10	616,000	16.60	765,000


Wire Rope 6x19 Class



6x25 Filler Wire with Fiber Core




6x25 Filler Wire with IWRC




6x26 Warrington Seal with IWRC

Size Rope Dia.	Fiber Core (IPS)		IWRC (EIPS)	
	Approx. Weight per Foot in Pounds	Breaking Strength in Pounds	Approx. Weight per Foot in Pounds	Breaking Strength in Pounds
1/4"	.105	4,940	.116	6,120
5/16"	.164	7,660	.18	9,480
3/8"	.236	10,980	.26	13,600
7/16"	.32	14,880	.35	18,360
1/2"	.42	19,260	.46	24,000
9/16"	.53	24,300	.59	30,200
5/8"	.66	30,000	.72	37,000
3/4"	.95	42,800	1.04	53,000
7/8"	1.29	48,000	1.42	71,600
1"	1.68	75,200	1.85	93,000
1.1/8"	2.13	94,600	2.34	117,000
1.1/4"	2.63	116,200	2.89	143,800
1.3/8"	3.18	139,800	3.50	172,800
1.1/2"	3.78	165,600	4.16	206,000
1.5/8"	4.44	192,600	4.88	238,000
1.3/4"	5.15	224,000	5.67	276,000
2"	6.72	288,000	7.39	314,000
2.1/4"	8.51	360,000	9.36	444,000
2.1/2"	10.50	440,000	11.6	544,000
2.3/4"	12.70	526,000	14.0	650,000
3"	15.10	616,000	16.60	765,000

Wire Rope 6x37 Class



6x36 Warrington Seal with Fiber Core



6x36 Warrington Seal with IWRC

Sizes above 1-1/2 are typically available on a special order basis.

All materials produced according to federal specifications RR-W-410D & RR-W-410E, preformed, right regular lay.