



Endless RoundUp™ RoundSlings

ENDLESS (ENR)

Liftex® Endless RoundUp™ RoundSlings are the most basic roundsling, yet they offer great versatility. Endless roundslings may be used in a vertical, choker or basket type hitch.

ADVANTAGES:


- Reduce cost with less total rigging weight
- Easy handling and storage
- Reduce risk of back and hand injuries
- Cover abrasion will not reduce capacity
- Provides a strong grip on loads
- Provides a tighter choke with an easier release
- Capacities are color coded

ENDLESS ROUNDSLING CAPACITY CHART

		Rated Capacity (lbs.)			Minimum Length	Approx. Diameter	Approx. WT / FT
	Part Number	Vertical	Choker	Basket			
PURPLE	ENR1	2,600	2,100	5,200	3'	.625"	0.3 LB
GREEN	ENR2	5,300	4,200	10,600	3'	.875"	0.4 LB
YELLOW	ENR3	8,400	6,700	16,800	3'	1.125"	0.5 LB
TAN	ENR4	10,600	8,500	21,200	3'	1.125"	0.6 LB
RED	ENR5	13,200	10,600	26,400	3'	1.375"	0.8 LB
WHITE	ENR6	16,800	13,400	33,600	6'	1.375"	0.9 LB
BLUE	ENR7	21,200	17,000	42,400	6'	1.625"	1.3 LB
ORANGE	ENR8	25,000	20,000	50,000	6'	1.750"	1.6 LB
ORANGE	ENR9	31,000	24,800	62,000	6'	2.125"	2.0 LB
ORANGE	ENR10	40,000	32,000	80,000	6'	2.350"	2.6 LB
ORANGE	ENR11	53,000	42,400	106,000	8'	3.150"	3.4 LB
ORANGE	ENR12	66,000	52,800	132,000	8'	3.950"	4.3 LB
ORANGE	ENR13	90,000	72,000	180,000	8'	4.800"	5.9 LB
ORANGE	ENR14	100,000	80,000	200,000	8'	5.520"	6.8 LB

* LARGER SIZES AVAILABLE





WARNING

SLING FAILURE CAN CAUSE
DEATH OR INJURY
SLING FAILURE RESULTS FROM
MISUSE, DAMAGE, AND
EXCESSIVE WEAR

ADHERE TO INDUSTRY
STANDARDS & REGULATIONS

HOW TO ORDER: PART NUMBER X LENGTH (LENGTH IS MEASURED BEARING POINT TO BEARING POINT)



WARNING

PROTECT SLINGS FROM CUTTING: Failure to protect sling from cutting may result in damage, injury or death. Contact us to discuss sling protection options.